

LIQUIDTIGHT CONNECTORS



L SERIES LIQUA-SEAL® CONNECTORS

L-Series Liqua-Seal Connectors are made of steel with a chromium zinc plating on the body, ferrule, locknut and clamp nut to prevent corrosion under the most adverse of conditions. Rated IP65, these connectors are UL Listed & CSA Certified with a watertight and oiltight design that provides strain relief and reduces stress on components and termination points. L-Series connectors are available in straight, 90° and 45° body styles and are also available with insulated throats and wire mesh grips. Die-cast zinc versions are also available.

L-Series Liqua-Seal Connectors are ideally suited for use in applications such as food processing plants, chemical processing facilities, offshore rigs, pulp and paper factories, automation equipment, heavy-duty electrical motor housings and medical equipment

Notes

Dimensional information on page G-52 in Tuff-Seal Technical Reference

ZINC-PLATED STEEL, STRAIGHT, EXTERNAL CONDUIT THREAD

PART NUMBERS

Conduit Size	Standard	Insulated Throat	With Mesh Grip	Insulated With Mesh Grip	Mesh Length
3/8"	LMM-01	LMM-02	LMM-01-E	LMM-02-E	2 5/8"
1/2"	LMM-11	LMM-12	LMM-11-E	LMM-12-E	3 7/8"
3/4"	LMM-21	LMM-22	LMM-21-E	LMM-22-E	4 3/8"
1"	LMM-31	LMM-32	LMM-31-E	LMM-32-E	5 1/4"
1 1/4"	LMM-41	LMM-42	LMM-41-E	LMM-42-E	5 5/8"
1 1/2"	LMM-51	LMM-52	LMM-51-E	LMM-52-E	5 3/4"
2"	LMM-61	LMM-62	LMM-61-E	LMM-62-E	7 1/2"
2 1/2"	LMM-71	LMM-72	—	—	—
3"	LMM-81	LMM-82	—	—	—
3 1/2"	LMM-91	LMM-92	—	—	—
4"	LMM-101	LMM-102	—	—	—

ZINC-PLATED MALLEABLE IRON, 45°, EXTERNAL CONDUIT THREAD

PART NUMBERS

Conduit Size	Standard	Insulated Throat	With Mesh Grip	Insulated With Mesh Grip	Mesh Length
3/8"	LMA-01	LMA-02	LMA-01-E	LMA-02-E	2 5/8"
1/2"	LMA-11	LMA-12	LMA-11-E	LMA-12-E	3 7/8"
3/4"	LMA-21	LMA-22	LMA-21-E	LMA-22-E	4 3/8"
1"	LMA-31	LMA-32	LMA-31-E	LMA-32-E	5 1/4"
1 1/4"	LMA-41	LMA-42	LMA-41-E	LMA-42-E	5 5/8"
1 1/2"	LMA-51	LMA-52	LMA-51-E	LMA-52-E	5 3/4"
2"	LMA-61	LMA-62	LMA-61-E	LMA-62-E	7 1/2"

ZINC-PLATED MALLEABLE IRON, 90°, EXTERNAL CONDUIT THREAD

PART NUMBERS

Conduit Size	Standard	Insulated Throat	With Mesh Grip	Insulated With Mesh Grip	Mesh Length
3/8"	LML-01	LML-02	LML-01-E	LML-02-E	2 5/8"
1/2"	LML-11	LML-12	LML-11-E	LML-12-E	3 7/8"
3/4"	LML-21	LML-22	LML-21-E	LML-22-E	4 3/8"
1"	LML-31	LML-32	LML-31-E	LML-32-E	5 1/4"
1 1/4"	LML-41	LML-42	LML-41-E	LML-42-E	5 5/8"
1 1/2"	LML-51	LML-52	LML-51-E	LML-52-E	5 3/4"
2"	LML-61	LML-62	LML-61-E	LML-62-E	7 1/2"
2 1/2"	LML-71	LML-72	—	—	—
3"	LML-81	LML-82	—	—	—
3 1/2"	LML-91	LML-92	—	—	—
4"	LML-101	LML-102	—	—	—

DIE-CAST ZINC

PART NUMBERS

Conduit Size	Straight Connector	90° Connector
3/8"	LTM-38	LTM-9038
1/2"	LTM-50	LTM-9050
3/4"	LTM-75	LTM-9075
1"	LTM-100	LTM-90100
1-1/4"	LTM-125	LTM-90125
1-1/2"	LTM-150	LTM-90150
2"	LTM-200	LTM-90200