

Battery Cable

Battery Cable – PVC Jacketed

- 100% copper conductors, finely stranded
- Black or Red PVC Insulation (Flexible)
- SAE specification J1127
- For applications up to 60 Volts
- Oil & acid resistant
- Excellent flame retardant characteristics
- Temperature Rating: -40°C to 90°C (-40°F to 194°F)

WHY CHOOSE PVC JACKETED BATTERY CABLE?

- ✓ Acid & Oil Resistant
- ✓ Flexible
- ✓ Durable
- ✓ Economical

i

B

Black

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	Bulk Spool*
6	.272"	7 x 19 x .014"	*669225	*769225	*769225B
4	.370"	7 x 27 x .014"	669226	769226	769226B
2	.460"	19 x 16 x .014"	*669227	*769227	*769227B
1	.495"	19 x 21 x .014"	*669228	*769228	*769228B
1/0	.550"	19 x 26 x .014"	*669229	*769229	*769229B
2/0	.595"	19 x 22 x .018"	669230	769230	769230B
3/0	.700"	19 x 35 x .016"	*669231	*769231	*769231B
4/0	.760"	19 x 54 x .014"	*669232	*769232	*769232B

*NEW

*NEW

*NEW

*NEW

*NEW

*NEW

*NEW



PVC Jacketed Battery Cable – Black

Red

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	Bulk Spool*
6	.272"	7 x 19 x .014"	*669242 (old p# 769233)	769242	769242B
4	.370"	7 x 27 x .014"	*669243 (old p# 769234)	769243	769243B
2	.460"	19 x 16 x .014"	*669244 (old p# 769235)	769244	769244B
1	.495"	19 x 21 x .014"	*669245 (old p# 769236)	769245	769245B
1/0	.550"	19 x 26 x .014"	*669246 (old p# 769237)	769246	769246B
2/0	.595"	19 x 22 x .018"	*669247 (old p# 769238)	769247	769247B
3/0	.700"	19 x 35 x .016"	*669248	*769248	*769248B
4/0	.760"	19 x 54 x .014"	*669249	*769249	*769249B

*NEW

*NEW

*NEW



PVC Jacketed Battery Cable – Red

Bulk Spools

GA	Black Part#	Red Part#	Approximate Bulk Spool Qty
6	*769225B	*769242B	2000' – 2500'
4	*769226B	*769243B	1500' – 2300'
2	*769227B	*769244B	500' – 1200'
1	*769228B	*769245B	500' – 1200'
1/0	*769229B	*769246B	500' – 1000'
2/0	*769230B	*769247B	500' – 1000'
3/0	*769231B	*769248B	300' – 1000'
4/0	*769232B	*769249B	300' – 600'

*NEW



* Call Techspan for exact spool lengths on cost saving bulk spools. Customers will be billed by the foot for the exact amount that is on the spool.