

## Loom & Tubing Accessories (Clamps, Clips)

Available  
in Black and  
Natural



Nylon Cable Clamps



Black Nylon Cable Clamps (Package Types)



Natural Nylon Cable Clamps (Package Types)



Nylon Push Mount Cable Clamps

### Nylon Cable Clamps

Techspan's 6/6 Nylon Cable Clamps are non-conductive and resist corrosion, salt, gasoline, oil, grease and common solvents. These clamps come in black or natural and have a maximum temperature rating of 85°C (185°F).

Width: 3/8" (9.5mm); Colour: Black

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
3/16" (4.3mm)	#10 .205" (5.2mm)		767500C
1/4" (6.3mm)	#8 .189" (4.8mm)	667076	767076C
5/16" (7.6mm)	#8 .189" (4.8mm)	667053	767053C
3/8" (8.7mm)	#8 .189" (4.8mm)	667054	767054C

Width: 3/8" (9.5mm); Colour: Natural

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
3/16" (4.3mm)	#10 .205" (5.2mm)		766500C
1/4" (6.3mm)	#8 .189" (4.8mm)	666076	766076C
5/16" (7.6mm)	#8 .189" (4.8mm)	666053	766053C
3/8" (8.7mm)	#8 .189" (4.8mm)	666054	766054C

Width: 1/2" (12.5mm); Colour: Black

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
1/8" (3.2mm)	#10 .205" (5.2mm)		767046C
1/2" (12.6mm)	#8 .189" (4.8mm)	*667047	767047C <b>*NEW</b>
5/8" (15.8mm)	#8 .189" (4.8mm)	667077	767077C
3/4" (19.4mm)	#8 .189" (4.8mm)	667078	767078C
1" (25.4mm)	#8 .189" (4.8mm)		767079C
1-1/8" (28.6mm)	#8 .189" (4.8mm)		767049C
1-1/4" (31.8mm)	#8 .189" (4.8mm)		767050C
1-1/2" (36.7mm)	#8 .189" (4.8mm)		767503C

Width: 1/2" (12.5mm); Colour: Natural

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
1/8" (3.2mm)	#10 .205" (5.2mm)		766046C
3/8" (9.5mm)	#8 .189" (4.8mm)		766502C
1/2" (12.6mm)	#8 .189" (4.8mm)	*666047	766047C <b>*NEW</b>
5/8" (15.8mm)	#8 .189" (4.8mm)	666077	766077C
3/4" (19.4mm)	#8 .189" (4.8mm)	666078	766078C
1" (25.4mm)	#8 .189" (4.8mm)		766079C
1-1/8" (28.6mm)	#8 .189" (4.8mm)		766049C
1-1/4" (31.8mm)	#8 .189" (4.8mm)		766050C
1-1/2" (36.7mm)	#8 .189" (4.8mm)		766503C

### Nylon Push Mount Cable Clamps

Quick and efficient installation. Base clip mounts in a .25" (6.4 mm) hole. Suitable for chassis and panels .020" to .090" (.50 mm to 2.3 mm) thick.

ID Size	25 PCS/PK
1/4" (6.4mm)	766080
3/8" (9.5mm)	766081
1/2" (12.7mm)	766082