


Silver Brazed Barrel

22-18 WIRE RANGE

.032 Stock

B

The silver brazed barrel style terminals and connectors are the basic butted seam style with a brazed barrel seam. Bonded with a special silver brazing alloy, this seam cannot possibly open under any conditions of stress or wire pull. The silver brazed barrel is guaranteed not to split and may be crimped from any direction. It is truly versatile. It can be crimped by many different methods and many different kinds of tooling. Ideal for both difficult-to-crimp solid wires and for stranded wires.



HEAVY DUTY TERMINALS made from 0.50" stock are designed to resist fractures under HEAVY vibration. Here is the best line of terminals for those extra difficult applications where RUGGEDNESS really counts!


Copper Solid and Stranded Wire Only





Stud Size Part Number


4-6  **R2A6S**


4-6  **R2A6**

6-8  **R2A8**

8-10  **R2A10**

12-1/4  **R2A14S**

1/4-5/16  **R2A56S**

5/16-3/8  **R2A38**

4-6  **BS2A6S**
Block Spade

4-6  **BS2A6**


8  **BS2A8**

Stud Size Part Number

10  **BS2A10**

Butt **B7A**

Terminals are NOT Actual Size See Sizing Chart on B-38, B-39



DIMENSIONAL CHART		
Part Number	W	L
B7A	0.660"	0.660"
BS2A10	0.312"	0.645"
BS2A6	0.292"	0.644"
BS2A6S	0.247"	0.626"
BS2A8	0.312"	0.653"
R2A10	0.312"	0.703"
R2A14S	0.460"	0.899"
R2A38	0.529"	0.950"
R2A56	0.530"	0.937"
R2A56S	0.477"	0.835"
R2A6	0.256"	0.646"
R2A6S	0.225"	0.550"
R2A8	0.313"	0.700"
R2A8S	0.264"	0.582"

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: See tool chart pages E-2,3,4

Economy installation tools: RAT-NINS, 453, HTS1000

See pages E-2 to E-4 for installation tools.



LISTED