| Product Name: | PH-ABT-HC-UCBI-0404 |
|---------------|--|
| | |
| Description: | Premier Pharmacy/Vaccine Undercounter Refrigerator Built-In 4.6 Cu. Ft. Capacity One solid swing door, right hinged* |
| | Microprocessor temperature controller |
| | Digital temperature display |
| | Audible and visual high and low temperature alarms |
| | Remote alarm contacts |
| | 2 probes; 1 in air and 1 in glycol bottle |
| | Adjustable operating temperature range: $36^{\circ}F - 46^{\circ}F (2^{\circ}C - 8^{\circ}C)$ Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm |
| | Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from being pushed against the back wall |
| | Back wall evaporator cover |
| | Vaccine storage power cord warning label |
| | Forced draft circulation |
| | Recessed door handle |
| | Keyed door lock |
| | Magnetic door gasket for positive seal Leveling legs |
| | Probe access port (3/8") |
| | Powder coat exterior |
| | High density urethane foam cabinet and door insulation |
| | HFC-free refrigerant (R600a), foam insulation and packaging |
| | Pharmacy refrigerator/freezer toolkit and temperature logs |
| | Two year parts and labor warranty, plus an additional three year |
| | compressor parts only warranty |
| | Pyxis [®] , Omnicell [®] and AcuDose RX [®] compatible |
| | Exterior dimensions: 23 ³ / ₄ "W x 24 ¹ / ₂ " D x 33 3/8 "H |
| | Cycle defrost |
| | 115V, 60 Hz, 1/8 HP, 1.74 Amps |
| | Energy Consumption 1.15 kWh/day UL/C-UL listed |
| | ENERGY STAR CERTIFIED |
| | Shipping weight: 137lbs. |
| | *This product is available left hinged, product number |
| | PH-ABT-HC-UCBI-0404-LH |